

Duo-Touch® II



Engineered and built to withstand the harshest field conditions, the MIL-STD 810F rugged Duo-Touch II is still lightweight and ergonomic. It's the rugged, weatherized Tablet PC to take to the real world where drops, spills and environmental extremes come with the territory.

Duo-Touch® II

Reliable

Providing for Computing - Anywhere, Anytime

- Meets or exceeds MIL-STD 810F and MIL-STD-3009
- ASTM 4169-99 truck assurance Level II, Schedule B
- Sealed against water and dust intrusion (IP54)
- Hazardous Location (HazLoc) Certification (UL1604)
- Magnesium alloy casing and impact absorbing exoskeleton

Innovative

For Today and for the Future

- DynaVue™ outdoor-readable display
- Intel® Core™ Duo Processor U2500 at 1.2 GHz
- Dual-mode active and passive touch screen
- 2GB DDRII SRAM 533MHz
- Optional integrated fingerprint scanner

The Smallest, Lightest Rugged Tablet PC

Services

We Know the Road

- Standard 3 yr limited warranty
- Expanded service options available

Wireless

Upgradable, Modular Design for Unparalleled Performance and Flexibility

- PC Radio card slot with optional sealed cover
- 802.11 a/g/n WLAN
- Bluetooth® 2.0
- Up to 3 RF modems and GPS at the same time
- Various combinations available depending on specific requirements

Ergonomic

Designed for Rugged Mobility

- One handed operation
- Under 2 kg (4.1lbs)
- Intuitive design for easy operation

GENERAL DYNAMICS
Itronix

Duo-Touch II Product Specifications



Durability Features:

- Die-cast magnesium for structural components
- Magnesium alloy casing and impact absorbing exoskeleton
- Operating temperature -20° to 60° C (-4° to 140° F)
- Storage temperature -55° to 75° C (-67° to 167° F)
- Boot Temperature -20° C with Hard Drive Heater
- Optional compliance with UL 1604 Class I, Division 2, Group A, B, C and D for hazardous locations
- Meets or exceeds MIL-STD 810F
- ASTM 4169-99 truck assurance Level II, Schedule B
- Sealed against water and dust intrusion (IP54)
- CE Mark

Operating System:

- Microsoft® Windows XP Tablet PC Edition 2005
- Microsoft® Windows Vista™

Processor/Memory:

- Intel® Core™ Duo Processor U2500 at 1.2 GHz, 2MB L2 Cache
- 2GB DDRII SDRAM 533 MHz

Display:

- 8.4" SVGA TFT Transmissive display with DynaVue™ patent-pending technology for optimum outdoor view ability
- DynaVue™ exceeds the minimum contrast ratio

Compact Size:

- Length: 10.6" (27.0 cm), Width: 7.2" (18.4 cm), Depth: 1.65" (4.2 cm)

Storage:

- Shock mounted 160 GB hard disk drive with heater

Weight:

- 4.1 lbs (less than 2.0 KG)

Power:

- Smart 3900 mAh (40.0WH) Lithium-Ion main battery pack
- 3900 mAh (40.0WH) Lithium-Ion expansion battery pack option

Pointing Device:

- Digitizer control panel touchscreen and passive touchscreen standard

Interfaces:

- (1) PC Card slot for Type I or II card with 32 bit Card Bus 2.1 Interface
- (1) Compact Flash slot for Type I or II card
- Built-in RJ-11 and RJ-45 jacks for integrated fax/modem and Ethernet
- (2) USB 2.0 connectors
- 26-pin docking connector
- Connector for expansion battery
- External speaker and microphone jacks

Integrated Wireline Communications:

- 56 Kbps V.92 fax/modem
- 10/100/1000 Mbit Base-T Ethernet LAN

Optional Integrated Wireless Communications:

- 802.11 a/g/n WLAN
- Bluetooth® 2.0
- GPS
- Sealed, rugged PC Card slot cover for user installed radios
- Up to 3 RF modems and GPS can be integrated at one time

Audio:

- Internal microphone and speaker
- PCI Audio with AC-97 compliance

Hot Keys:

- Enter
- Up/Down Arrows
- Escape
- Function Key
- Security (Secure Attention Sequence)
- Rotate Display Image (landscape/portrait)
- On/off switch for all radios
- Suspend/Power on/off
- WLAN/Bluetooth on/off

Options:

- Desk Mount with 15-pin external video (CRT) port, (2) USB ports, and expansion Battery Charger
- 12 / 24VDC vehicle power supply
- Vehicle dock with serial, USB, and external monitor connections
- Fingerprint Scanner
- Hand strap
- Carry cases for system and accessories with handle and optional shoulder straps
- Backlit keyboard

Warranty

- 3 yr limited
- Extended service and maintenance options available

GENERAL DYNAMICS Itronix

North America Head Office: 1000 Sawgrass Corporate Parkway • Suite 300 • Sunrise, FL 33323 • Tel: +1-800-441-1309, +1-954-846-3400 • Fax: +1-954-846-3392 • Email: sales@gd-itronix.com • www.gd-itronix.com

EMEA Head Office: Earlsplace Business Park, Fletchamstead Highway, Coventry, CV4 9UR UK • Tel: +44(0) 24 7671 4800 • Fax: +44(0) 24 7671 5677 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

Germany: Tel: +49 211 5 23 91 459 • Fax: +49 211 5 23 91 200 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

France: Parc d'Affaires Silic, 74 Rue d'Arcueil, BP 10405, 94573 RUNGIS Cedex, France • Tel: +33(0) 1 46 87 80 09 • Fax: +33(0) 1 45 60 55 95 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

Asia: 7F, No. 2, Lane 258, Rueiguang Road, Taipei 114, Taiwan • Tel: +886 2 8797 7080 • Fax: +886 2 8797 7081 • Email: sales@gd-itronix.com.tw

© 2010 General Dynamics. All rights reserved. General Dynamics Itronix Corporation reserves the right to make changes in its products and specifications at anytime and without notice. All trademarks indicated as such herein are trademarks of General Dynamics Itronix. All other product and service names are the property of their respective owners. ® Reg. U.S. Pat. and Tm. Off. Duo-TouchIIv052010